

OPTIONAL METAL  
COPING ASSEMBLY

TAKE ENTIRE SYSTEM  
COMPLETELY OVER  
TOP OF PARAPET

FINISH COAT COMPONENT OVER  
ENTIRE ROOF (2 COATS).  
FINISH IN SPECIFIED COLOR.

PARAPET WALL

TAKE 12" WIDE FOUNDATION COAT,  
FABRIC, AND FOUNDATION COAT  
COMPONENTS UP CANT AND  
TERMINATE VERTICALLY ON PARAPET

FOUNDATION COAT, FABRIC, AND  
FOUNDATION COAT COMPONENTS

ROOF DECK AND INSULATION  
SYSTEM WITH OR WITHOUT  
CANT STRIP

NOTES:

1. ALL FLASHING SHALL BE DESIGNED FOR THE APPLICABLE CONDITIONS. METAL THICKNESS, FASTENERS, AND LAPPING SHALL BE AS SPECIFIED BY THE ROOF DESIGNER.
2. REFER TO THE SPECIFICATIONS FOR SPECIFIC EXECUTION REQUIREMENTS.
3. PREMIUM COAT SYSTEM- FOUNDATION COAT, FABRIC, FOUNDATION COAT, AND FINISH COAT COMPONENTS.
4. FOUNDATION COAT- COMBINED COVERAGE (2 COATS) AT MINIMUM RATE OF 40 SF/GALLON.
5. FINISH COAT- COMBINED COVERAGE (2 COATS) AT MINIMUM RATE OF 70 SF/GALLON.
6. PRIMING- REFER TO HYDROSTOP SPECIFICATIONS FOR DECK PRIMING REQUIREMENTS.

**HYDRO  
STOP**

**PREMIUM COAT SYSTEM**

WALL FLASHING DETAIL  
10 YEAR SYSTEM

DATE:

08/20/10

SHEET No :

**WF-1-10**