



# Technical Data Sheet

## SureBond Primer

Product # 2000-002 & 2000-005

Updated – June 30, 2011

### DESCRIPTION

**SureBond Primer** is a water based pure Acrylic primer used for sealing all types of masonry, metal and chalky surfaces.

### RECOMMENDED USES

- Surface Primer for all types of masonry (brick, block, stucco, and concrete).
- Surface Primer for old chalky paint

### ADVANTAGES & BENEFITS

- Extremely U.V. resistant
- Resists acid rain and chemical pollutants to protect from chemical spills and fall-out damage
- Meets V.O.C. emissions and regulations to eliminate facility downtime during installation.
- Nontoxic formulation is safe to apply
- Easy application and cleanup
- No special training or equipment required to install

### PRODUCT CHARACTERISTICS

VOC:	141 gm/lt
Vol. Solids:	22.99%
Weight Solids:	25.13%
Density:	8.5431 lbs/gal

pH: 9.2

### APPLICATION INSTRUCTIONS:

#### Surface Preparation

As a minimum, clean and prepare surfaces to receive waterproofing by removing all loose and flaking particles, grease and laitance with the use of a stiff bristle push broom and or washing. Care should be taken not to inject water into the substrate during washing. In some cases additional drying time may be required after the cleaning process. Please consult your Hydro-Stop Inc. Technical Sales Representative for additional advice on cleaning various roofing substrates.

New concrete should be allowed to cure for at least 28 days before applying **SureBond Primer**.

#### Application

**SureBond Primer** comes ready to use; however, it is recommended that the container be shaken or stirred before application.

Apply **SureBond Primer** by brush or roller to area to the recommended coverage rate. Allow to dry before proceeding with additional products.

#### Coverage

Coverage may vary due to porosity of substrate. The average surface will use 250-400 square feet per gallon.

Coated Brick: 300 ft.<sup>2</sup>/gal.  
(6.9 m<sup>2</sup>/L)

Stucco: 250 ft.<sup>2</sup>/gal.  
(5.75 m<sup>2</sup>/L)

Painted Surface: 400 ft.<sup>2</sup>/gal.  
(9.2 m<sup>2</sup>/L)

Block: 250 ft.<sup>2</sup>/gal.  
(5.75 m<sup>2</sup>/L)

Split-Faced Block: <200 ft.<sup>2</sup>/gal.  
(<4.6 m<sup>2</sup>/L)

### SAFETY & HANDLING

For specific information regarding safe handling of this material please refer to the Material Safety Data Sheet (MSDS).

**SureBond Primer** can be used in a safe and environmental friendly manner. It is designed to reduce the output of V.O.C.'s while providing the customer with a high performance primer.

For more information: *Contact your Hydro-Stop technical department.*

### CLEAN UP

Thoroughly rinse application equipment with clean water.

### ORDERING INFORMATION

**SureBond Primer** can be purchased in two gallon or five gallon pails at any official distributor of Hydro-Stop. For a distributor in your area please call us at 1-800-739-5566.