

NOTE: OVER BARE CONCRETE COVER WITH "BARRIERGUARD" SLURRY @ RATE OF 200 SF/GAL.

LAP PREMIUM COAT SYSTEM COMPONENTS FROM THE ROOF FIELD OVER EDGE DETAIL.

FOUNDATION COAT, 12" FABRIC, AND FOUNDATION COAT COMPONENTS.

PREMIUM COAT SYSTEM: FOUNDATION COAT, 40" FABRIC, FOUNDATION COAT, AND TWO COATS OF FINISH COAT INSTALLED OVER ENTIRE ROOF FIELD.

8"

COVER ENTIRE EXPOSED EDGE

WALL

CONCRETE ROOF DECK

NOTES:

1. ALL FLASHING SHALL BE DESIGNED FOR THE APPLICABLE CONDITIONS. METAL THICKNESS, FASTENERS AND LAPPING SHALL BE AS SPECIFIED BY THE ROOF DESIGNER.
2. REFER TO THE SPECIFICATIONS FOR SPECIFIC EXECUTION REQUIREMENTS.
3. PREMIUM COAT SYSTEM- FOUNDATION COAT, FABRIC, FOUNDATION COAT, AND FINISH COAT COMPONENTS.
4. FOUNDATION COAT- COMBINED COVERAGE (2 COATS) AT MINIMUM RATE OF 40 SF/GALLON.
5. FINISH COAT- COMBINED COVERAGE (2 COATS) AT MINIMUM RATE OF 70 SF/GALLON.
6. PRIMING- REFER TO HYDROSTOP SPECIFICATIONS FOR DECK PRIMING REQUIREMENTS.



PREMIUM COAT SYSTEM

CONCRETE ROOF DECK EDGE DETAIL
WITHOUT METAL DRIP EDGE
10 YEAR SYSTEM

DATE:

08/26/10

SHEET No :

DE-3-10